Performance Analysis of ML Based Techniques for MPPT under Various Shading Pattern

Synopsis submitted to the IIMT University in partial fulfillment of the requirements for the award of the Degree of

DOCTOR OF PHILOSOPHY

In

Electrical & Electronics Engineering

By

(Zaiba Iishrat)

Full time

Under the guidance of

Dr. Ankur Kumar Gupta
&
Dr. Seema Nayak (Co-Guide)

School of Engineering & Technology
IIMT University, Meerut

IIMT University, Meerut

School of Engineering & Technology/ Deptt. of Electrical and electronics Engineering/IIMT University)

Introduction: These days, deteriorating quantity of conventional power assets, it is essential to produce the extra energy from non conventional power resources, out of that solar energy is main. It will unquestionably get more affordable in the coming years and evolve into a more advanced technology in terms of cost and applications. Earth receives more sunshine each day than (around 1366W). There is no cost associated with using this limitless energy source. The prime advantage of photo energy as compare to other energy sources is the direct conversion of photon light into electrical energy using the tiniest photo-voltaic (PV) solar unit [1]. A tremendous amount of research has been done to harness the solar's energy by designing solar unit, panels, and modules with exceptional translating shapes. One of the key payback of solar power is that it is available to everyone for free and in large amounts, unlike the worth of different fossil fuels and oils in the past decade. Moreover, compared to conventional energy invention technology, solar energy requires alarmingly less human labour. Sun energy has a significant potential to help meet the global need for electricity, particularly in nations with abundant sun radiation. The projected increase in solar energy power from 227 GW in 2015 to 1362 GW by 2030 seems promising. This source includes dispersed generation on building roofs as well as huge solar farms or parks [8].

The development of solar PV production has progressed unexpectedly thus far, with significant achievements made in current times in terms of installations (including off-grid), charge deductions and industrial breakthroughs, as well as the establishment of important photon energy relationships. Undoubtedly, photon energy will remain a crucial green choice in the future.

The PV system still has considerable limitations despite its advantages. A PV system operates at very low levels of efficiency without an MPPTC. In order to get the peak power out of a PV-S, an MPPTC was necessary. The bulk of MPPT algorithms have been presented to track MPP in a solar system [4]. However, under PSC, several MPPT tactics were unable to follow GMPP. As a result, the PV system experienced power losses and operated with low efficiency [5, 6].

The VI or VP features graph of PV cell is nonlinear and it is varied by the outcome of sun irradiance, temperature and dust effect Figure 1. In solar PV panel battery is expensive component, if it is connected directly with PV module. The most expensive components of standalone solar PV set up are the batteries and PV modules. As there is no fortification against overcharge when the batteries are connected directly to the PV system, the battery life span decreases. Batteries can be protected from overcharging even though standard charge controllers cannot operate PV model at PPP, consequential in reduced efficiency [2]. To maximize competence, it is best to run the P-V setup at its max response in organize to supply the batteries with the most electricity.

The current voltage (IV) characteristic of a PVarrangement under constant uniform irradiation resembles that in Fig. 1. The array functions most efficiently and generates the most output power at a precise position on the curvature recognized as the peak power point (PPP). The operational point of a P-V array that is straightly coupled to a RL (also known as a DC system") is where the P-V array's I-V curve and the load line converge in Figure 2. Generally speaking, as shown in the diagram, this operating point is not at the PPP of the P-V array. To ensure that the load's power requirements can be met in a direct-coupled system, the PV array must often be larger. This method increase the cost of overall panel.



Figure 1. VI and PV characteristics of solar panel under uniform condition

Due to the effect of variable metrological condition the received power from photo panel is not constant. Photo system should be operate at peak point to obtain peak power there for MPPTC required[21–23].It is tough to locate the peak point so several research have been done to achieve max power. The MPPT accomplishes this by autonomously controlling the load and PV array's voltage or current. If the PV array's PPP is handled properly, the MPPT algorithm can find and track it. However, the PPP's location in the IV plot is not known earlier. It must be identified either through model computations or a search approach. The problem is made more challenging by the nonlinear dependency of the PPP on temperature and illumination, as shown in Fig. 2. The PV I-V curves for increasing illumination at constant temperature are given in Fig. 2 and fig 3.



Figure 2. VI characteristics under variant solar radiation[20]



Figure 3. P-V characteristics under variant solar radiation [20]

Diverse DC-DC converter tactics are utilized to forward the utmost power from PV system to loads or batteries in this situation, and MPPT approaches play a key role in maximizing output power from PV modules figure 4.



Figure 4 . PV Panel with MPPT Controller

Because solar radiation is dynamic, power production is unsteady all day long. Additionally, the incorporation of renewable energy sources with the different electrical systems and partial radiation on photo panel results in numerous sufferers that are significant adequate to take into account even during the design stage for driving a specific load [2]. Due to all of these

restrictions, the efficiency still ranges between 14% and 16%. When more than 71 Japanese PV systems were surveyed by a university in Tokyo, the solar loss percentage was about 25% [9].

Due to fractional shade caused by surrounding structures, plants, houses, dust, etc., the PV array's PV modules of a Photo-energy generation system may function in conditions of non-uniform incidence solar irradiation. The PV array's power-voltage curve shows a large number of local maximum power points (MPPs) under these conditions. Out of these LMPP there will be only one prime peak power point at which highest power will be extract from solar modules [2].Under the varying weather situation, the MPPT controller should use an effective tracking techniques to follow the global energy tip for extracting the highest power from photo set up.

Literature Review:

There are many classical tactics like perturbation and observation (P&OA), incremental-conductance (INCA), short circuit current method and open circuit voltage method etc but these techniques shows the lesser output power due to subsistence of several local utmost power points. The evolutionary algorithms based on ML have also been applied, to obtain the GMPP for the response of the PV module is enhanced. The benefit of these algorithms is that, in contrast to the laborious scanning/sweeping method, they can search for the locality of the universal peak power point at the VP graph of the PV generator with less search steps.

Fuzzy logic controller (FLC) [10,11], artificial neural network (ANN) [12], and neuro-fuzzy (NF) [13] are examples of artificial intelligence methods for MPPT implementation. These techniques can reach a PV system's global maximum under irregularities in temperature and irradiance. However, the FLC technique has to create an exhaustive fuzzy law chart, the ANN scheme needs to instruct analogous neural network grids, and the NF method needs to precisely construct a neuro-fuzzy model. Therefore, in order to perform MPPT, these algorithms must use more memory and require longer computation times.

Swarm optimised algorithms have been successful in gaining the interest of academics in recent years. Particle swarm optimisation (PSO), cuckoo search (CS), firefly algorithm (FA), and genetic algorithm (GA) are some of the regularly used swarm optimised methods. Under unfavourable irradiance and temperature conditions, these approaches can implement MPPT for the PV array. However, the GA technique has a difficult computation procedure and needs a lot of parameters, including mutation, chromosomal selection, and crossover rate. Multiple parameters must be modified when using the PSO approach, and the particles update too quickly for them to keep diversity in loss. Ideal following effect and fast convergence rate are features of the CS and FA methods, however once they reach the MPP region, they lack unpredictability. To extract the PPP under partial lighting, classical techniques and swarm optimisation algorithms are frequently combined. For example, PSO and P&O [17] combine, while GA and P&O in [18] integrate. Even while both algorithms supply the variability necessary for optimisation, the two-stage optimising approaches make MPPT more difficult.

Mounil et. all [3] proposed ML based multivariate linear regression algorithm in preexisting P&O method and increase the efficiency of hybrid model up to 99.8% and decrease the convergence time to achieve the Maximum power point as compare to conventional method.

Author considered three input parameters to train the models that was solar irradiance, temperature and Humidity and used the python for simulation therefore the number of iteration was 1000 corresponding to 83 hour of training of ML model which is quiet long time period to train the model.

A thorough evaluation of the categorization and action of the six main smart MPPT techniques that are AI, FLC, ANN, GA, SI, and ML was proposed by Kah Yung Yap et al. On the basis of the review and the outcomes of the MATLAB/Simulink simulation, work has been proposed. Despite the fact that all MPPT algorithms exhibit good convergence under PSC or quick changes in irradiance, these methods are more expensive, hard to design, and use more datasets than traditional MPPT methods.

The forecasting of photo energy generation by means of machine learning including and excluding MPPTC was proposed by Debottam Mukherjee et al. [5]. The study was conducted in the Indian city of Badabenakudi, Orissa. Coarse Tree is the finest model for forecasting of PVenergy generation with an MPPTC and RMSE of 1.675, and Rational Quadratic Gaussian Process Regression (RQGPR) is the finest model for forecasting photon power generation without an MPPTC, with RMSE 1.628.

In order to follow the max energy end (PPP) of photo set-up, Ruhi et all[6] proposed a supervised MLA based on NN to track the MPP for smaller data, supporting the diverse train data set. According to the theoretical findings, the enhanced NN MPPT algorithm is more efficient than the P&OT technique in the same surroundings, and the photo system may continue to operate at MPP without oscillation or the risk of making any kind of error. As a result, it can prevent power loss near the MPP in addition to reducing errors in judgment. This technique use Bayesian regularization method to train the model which is best for smaller data set**.**

In order to exploit the energy output of a P-V setup when its P-V arrangement is operating under PSC, Christos Kalogerakis et al. [7] proposed a GMPPT process for finding the setting of the crest position in the shortest amount of investigate time. In contrast to the convergence duration needed for a global point track procedure depend on the particle swarm optimization (PSO) method, this work provides a revolutionary Q-learning-based GMPPT technique. This techniques offers searching time of GMPP under various shading pattern is reduced by 80.5-98.3% but offers less MPPT efficiency as compare to PSO algorithm. The convergence duration and number of finding step is more for initial partial shading pattern but it start to reduce after learning from different patterns.

Gap Identification: There are many conventional MPPT techniques like P&OA,INCA, VOCA, and ISCA etc.

- The universal peak power point (UPPP) cannot be finding out in partial shading environment (PSC).
- There is only one UPPP and copious minor peak power points (PPPs) on the P-Vcurvature of a solar setup.
- The incorporation of ML in MPPT allows the finding of chief maximum power point while escalating the overall effectiveness of conventional MPPT technique by decreasing

the search time to achieve the MPP and harnessing of maximum power of solar panel at MPP under variable solar irradiance condition.

Objective:

1. Implementation of ML technique in existing MPPT method to accomplish the UPPP and compare the efficiency of photo system with conventional MPPT method and ML based hybrid method.
2. Comparative study of different ML used PPPT tactics for photo system under different solar irradiance condition.
3. Design and development of ML based MPPT technique to achieve the MPP in minimum time and less number of search iteration.

References:

1. Lai, C.S.; McCulloch, M.D. Levelized cost of electricity for solar photovoltaic and electrical energy storage Appl. Energy 2017, 190, 191–203.
2. Koutroulis, E.; Blaabjerg, F. Overview of maximum power point tracking techniques for photovoltaic energy production systems. Electr. Power Compon. Syst. 2015, 43, 1329–1351.
3. Mounil Memayaa, C. Balakrishna Moorthyb, Sahitya Tahilianic, Siddarth Sreenid," Machine learning based maximum power point tracking in solar energy conversion systems", International Journal of Smart Grid and Clean Energy", doi: 10.12720/sgce.8.6.662-669.
4. Kah Yung Yap, Charles R. Sarimuthu, and Joanne Mun-Yee Lim," Artificial Intelligence Based MPPT Techniques for Solar Power System: A review", JOURNAL OF MODERN POWER SYSTEMS AND CLEAN ENERGY, VOL. 8, NO. 6, November 2020.
5. Debottam Mukherjee,Samarat Chakarabotry,Pabitra Kumar ," Machine Learning based Solar Power Generation Forecasting with and without MPPT Controller","IEEE International Conference for convergence in Engineering 2020".
6. Ruhi Sharmin, Sayeed Shafayet Chowdhury, Farihal Abedin, and Kazi Mujibur Rahman," Implementation of MPPT Technique of Solar Module with Supervised Machine Learning".
7. Christos Kalogerakis , Eftichis Koutroulis and Michail G. Lagoudakis," Global MPPT Based on Machine-Learning for PV Arrays Operating under Partial Shading Conditions", Appl. Sci. 2020, 10, 700; doi:10.3390/app10020700.
8. D. Sera, T. Kerekes, R. Teodorescu, and F. Blaabjerg, "Improved MPPT algorithms for rapidly changing environmental conditions," in 2006 12th International Power Electronics and Motion Control Conference,Portoroz, 2006, pp. 1614–1619.
9. K. Kurokawa, et al., "Sophisticated verification of simple monitored data for Japanes field program," in 2nd World Conference and Exhibition on Photovoltaic Solar Energy Conversion, Vienna, Austria,1998, pp. 1941–1946.
10. Altas, I.H.; Sharaf, A.M. A novel maximum power fuzzy logic controller for photovoltaic solar energy systems. Renew. Energy 2008, 33, 388–399.

11. Gounden, N.A.; Peter, S.A.; Nallandula, H.; Krithiga, S. Fuzzy logic controller with MPPT using line-commutated inverter for three-phase grid-connected photovoltaic systems. Renew. Energy 2009, 34, 909–915.
12. Liu, Y.H.; Liu, C.L.; Huang, J.W.; Chen, J.H. Neural-network-based maximum power point tracking methods for photovoltaic systems operating under fast changing environments. Sol. Energy 2013, 89, 42–53.
13. Kharb, R.K.; Shimi, S.; Chatterji, S.; Ansari, M.F. Modeling of solar PV module and maximum power point tracking using ANFIS. Renew. Sustain. Energy Rev. 2014, 33, 602–612.
14. Shaiek, Y.; Smida, M.B.; Sakly, A.; Mimouni, M.F. Comparison between conventional methods and GA approach for maximum power point tracking of shaded solar PV generators. Sol. Energy 2013, 90, 107–122.
15. Ishaque, K.; Salam, Z.; Amjad, M.; Mekhilef, S. An improved particle swarm optimization (PSO)–based MPPT for PV with reduced steady-state oscillation. IEEE Trans. Power Electron. 2012, 27, 3627–3638.
16. Ishaque, K.; Salam, Z. A deterministic particle swarm optimization maximum power point tracker for photovoltaic system under partial shading condition. IEEE Trans. Ind. Electron. 2013, 60, 3195–3206.
17. Ahmed, J.; Salam, Z. A maximum power point tracking (MPPT) for PV system using cuckoo search with partial shading capability. Appl. Energy 2014, 119, 118–130.
18. Teshome, D.; Lee, C.H.; Lin, Y.W.; Lian, K.L. A modified firefly algorithm for photovoltaic maximum power point tracking control under partial shading. IEEE J. Emerg. Sel. Top. Power Electron. 2017, 5, 661–671.
19. Sundareswaran, K.; Kumar, V.V.; Palani, S. Application of a combined particle swarm optimization and perturb and observe method for MPPT in PV systems under partial shading conditions. Renew. Energy 2015, 75, 308–317.
20. Daraban, S.; Petreus, D.; Morel, C. A novel MPPT (maximum power point tracking) algorithm based on a modified genetic algorithm specialized on tracking the global maximum power point in photovoltaic systems affected by partial shading. Energy 2014, 74, 374–388.
21. Altas IH, Sharaf AM. A solar powered permanent magnet DC motor drive scheme. In: Proceedings of the 17th annual conference of solar energy society of Canada, Toronto, Ontario, Canada; 1991. p. 65–7.
22. Sharaf AM, Wang L. A photovoltaic powered efficient DC motor drive for pump irrigation. In: Proceedings of the Canadian solar energy conference, Halifax, N.S., Canada; 1990.
23. Hohm DP, Ropp ME. Comparative study of maximum power point tracking algorithms. Progress in Photovoltaics: Research and Applications 2003;11:47–62, http://dx.doi.org/10.1002/pip.459.